




Part Name:	Date: 06/02/2026
Part #: in PC035-180-7130-SST-0415-C-N-IN	
(Click to see Part # on Website)	
Spring Type: Compression Spring	End Type: Closed End
Finish: None	Direction of Wind: Right Hand
Material: Stainless 302 ASTM A313	Spring Index (I): 4.143
Weight / M: 0.903 Lbs	Length of W: 3.248 in

Physical Dimensions	IN	MM	Tolerances (in)
Wire Diameter (WD)	0.035 in	[0.889 mm]	+/- 0.001
Outer Diameter (OD)	0.180 in	[4.572 mm]	+/- 0.005
Mean Diameter (MD)	0.145 in	[3.683 mm]	+/- 0.005
Inner Diameter (ID)	0.110 in	[2.794 mm]	+/- 0.005
Free Length (FL)	0.415 in	[10.541 mm]	+/- 0.015
Active Coils (AC)	5.130	5.130	+/- 1/4 Coil
Total Coils (TC)	7.130	7.130	+/- 1/4 Coil
Solid Height (SH)	0.285 in	[7.239 mm]	+/- 0.020
Coil Pitch (CP)	0.060 in	[1.534 mm]	
Rise Angle (RA)	7.556	[7.556]	
Spring Rate (K)	119.33313 lbs/in	20.898 N/mm	+/- 11.933
Max Load (ML)	11.095 lbf	49.354 N	+/- 1.109
Max Travel (MT)	0.093 in	2.362 mm	
Material Shear Modulus (G)	9949475.938 PSI	68599221788.087 Pa	
Max Shear Stress Possible (t max)	132540.000 PSI	913831131.614 Pa	
Wahl Correction Factor (W)	1.387	1.387	



Notes	Scale: 11.667	Revision #:	Drawn By:	Approved By:
This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. Access Spring makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specification.				This Drawing is the property of ACCESS  SPRING It may contain confidential, proprietary information, that is Access Spring property. Do not disclose to or duplicate for others except as authorized by Access Spring.