




Part Name:	Date: 06/02/2026
Part #: in (Click to see Part # on Website)	PT125-750-5375-SST-RH-0474-N-IN 
Spring Type: Torsion Spring	Material: Stainless 302 ASTM A313
Finish: None	Direction of Wind: Right Hand
Weight / M: 40.794 Lbs	Length of W: 11.502 in
Spring Index (I): 5.000	

Physical Dimensions	IN	MM	Tolerances (in)
Wire Diameter (WD)	0.125 in	[3.175 mm]	+/- 0.001
Outer Diameter (OD)	0.750 in	[19.050 mm]	+/- 0.015
Mean Diameter (MD)	0.625 in	[15.875 mm]	+/- 0.015
Inner Diameter (ID)	0.500 in	[12.700 mm]	+/- 0.015
Length Leg 1 (LL1)	0.474 in	[12.040] mm	+/- 0.040
Length Leg 2 (LL2)	0.474 in	[12.040] mm	+/- 0.040
Total Leg Length (TLL)	0.948 in	[24.079] mm	+/- 0.040
Total Coils (TC)	5.375	5.375	+/- 1/8 Coil
Body Length (BL)	0.797 in	[20.244 mm]	+/- 0.025
Free Position (FP)	135 Deg	135 Deg	
Rate per Degree	0.47796 in-lbs/Deg	54.000 N-mm/Deg	+/- 0.048
Max Torque	27.128 in-lbs	3064.933 N-mm	+/- 2.713
Max Travel (MT)	56.758 Deg	56.758 Deg	
Material Shear Modulus (G)	9949475.938 PSI	68599221788.087 Pa	
Max Shear Stress Possible (t max)	28969.824 PSI	199739906.335 Pa	
Wahl Correction Factor	1.310	1.310	



Notes	Scale: 1.333	Revision #:	Drawn By:	Approved By:
This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. Access Spring makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specification.				This Drawing is the property of ACCESS SPRING It may contain confidential, proprietary information, that is Access Spring property. Do not disclose to or duplicate for others except as authorized by Access Spring.